

22 finishes

Woodvents Louvres

THE COLLECTION

Woodvents Louvres

Slatted louvre panels that let a space breathe. A deep, evenly pitched groove profile in warm oak, teak and weathered-grey tones – built for full-height feature walls, ceilings and partition screens where rhythm matters more than ornament.

Every finish is held against the code printed beneath it. Quote the code and the profile when raising an enquiry, and order the full quantity against a single production batch – shades vary slightly between runs.

Water resistant Suited to kitchens, wash areas and covered balconies; will not swell like MDF.	Termite resistant The composite core carries no cellulose food source.	Fire resistant Self-extinguishing formulation; certificates available on request.
Colour stability UV-stable decor layer holds its tone in daylight interiors.	Anti-fingerprint Low-sheen face resists marking on high-traffic surfaces.	Easy to clean Damp cloth and mild detergent; no wax or polish required.

PROFILE	PANEL	THICKNESS	FINISHES
L-15 / L-16	2900 × 225 / 228 mm	11 / 6 mm	22

L-15 • Wide Groove

PANEL 2900 × 225 × 11 MM



L15-140

L-15



L15-139

L-15



L15-142

L-15



L15-138

L-15



L15-141

L-15



L15-137

L-15



L15-145

L-15



L15-147

L-15



L15-143

L-15



L15-146

L-15



L15-144

L-15



L15-148

L-15



L-15 SECTION · 225 × 11 MM

L-15 / L-16 • Fine Groove

PANEL 2900 × 228 × 6 MM



L15-150

L-15 / 16



L16-159

L-15 / 16



L16-158

L-15 / 16



L16-143

L-15 / 16



L16-157

L-15 / 16



L16-164

L-15 / 16



L16-160

L-16



L16-163

L-16



L16-161

L-16



L16-162

L-16



L-16 SECTION · 228 × 6 MM

REFERENCE

Sizes & fixing

PROFILE	NOMINAL SIZE	APPLICATION
Woodvents L-15	2900 × 225 × 11 mm	Louvre — wide groove, full-height walls and ceilings
Woodvents L-16	2900 × 228 × 6 mm	Louvre — fine groove, curved and column applications

INSTALLATION

Fix with adhesive on a true, dry substrate, or mechanically to a battened frame at 400–600 mm centres. Allow material to acclimatise on site for 24 hours before installation. Set out from the most visible corner so any cut panel lands where it will be least seen. Retain offcuts from the same batch for later repair.

CARE

Clean with a damp cloth and mild detergent. Avoid solvents, abrasive pads and steam. No wax, oil or polish is required at any point in the life of the panel.



Premium interior and exterior surface materials
— supplied, detailed and installed.

VISIT

1st Floor, 13C Paul Mansions
6 Bishop Lefroy Road, opp. Tata Tea
Near Rabindra Sadan
Kolkata 700020, West Bengal

CONTACT

+91 98300 20010
thinkwood.ashish@gmail.com
thinkwood.in

FOLLOW

Instagram @thinkwood.in
Facebook /thinkwoodofficial

SAMPLES

Physical samples of every code in
this book are available on request.
Site mock-ups can be arranged for
orders above 500 sq ft.

BILLING ENTITY

Altius Realty Services
Kolkata